

MAGFIRE

Technical Specification



Product Code: MAGPRO-HD1

Luckinslive 399178740

Description: Addressable Heat Detector



General Information

Dimensions (mm)	ø103 x 42
Colour	White
Materials	Housing: ABS
Available Classes (Selected from CIE)	A1R/A2S/BS
Weight (Kg)	0.11
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	15 - 30
Nominal Operating Voltage (V DC)	27
Consumption in quiescent state, no communication (µA)	<160 (@27V DC)
Consumption in quiescent state, with communication (µA)	< 200µA (@27V DC)
Consumption in alarm state, with communication (mA)	6.5
Maximum Output in alarm state at terminal RI (mA)	7.5 (7.5V)

Inputs & Outputs

Maximum Output in alarm state at terminal RI (mA)	7.5 (7.5V)
---	------------

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP30
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products Compatible with MAGPRO-DB, MAGPRO-DBS and MAGPRO-DBSS

Accessories

- MAGPRO-DB: Detector Base
- MAGPRO-DBS: Detector Base with Sounder
- MAGPRO-DBS: Detector Base with Combined Sounder Strobe

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN