

MAGFIRE

Technical Specification



Product Code: MAGPRO-REP01

Luckinslive 437611512

Description: Addressable Repeater Panel



General Information

Dimensions (mm)	200 x 330 x 48
Colour	Grey
Materials	Housing: ABS
Maximum Number of Events in Log	10,000
Maximum Distance to Fire Panel (m)	1,000
Maximum Number of Networked Panels	64
Type of Network	Loop
Connection for Firmware Update(s)	Micro USB
Compatibility - MAGPRO16	Version 4.5.2 or Higher
Compatibility - MAGPRO96	Version 6.7.2 or Higher
Weight (Kg)	0.5
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	24 (± 4)
Maximum Cable Size (mm²)	2.5
Maximum Current Consumption	0.4A

Communication

Communication Type	RS-485
Connection for Firmware Update(s)	Micro USB
Display	7" TFT Touchscreen
Clock	Realtime
User Interaction	Touchscreen GUI

Environment

Ingress Protection	IP40
Operating Temperature (°C)	-5 to +40
Storage Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	95

Compatible Products Compatible with MAGPRO series of CIE's

Additional Information MAGPRO16/G requires Firmware version 4.5.2 or above
MAGPRO96 requires firmware version 6.7.2 or above
MAGPRO9601 requires firmware version 1.1.4 or above

Features

- Slim design
- Reset/Evacuate/Silence Sounders and Buzzers of all network panels
- Multilanguage support
- Changeable company logo on main standby screen
- Optional redundant network connection

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN