




MATT BLACK MONITORED DOOR STATUS DOUBLE SLIMLINE MAGNETIC LOCK (600LB)

RALock

FIRE TESTED to
BSEN1634-1:2014 & BS476:Part22:1987
(30, 60, 90 & 120 min timber door-sets)



MBK-ML600-D-MDS



Fire tested range of maglocks and brackets
from a market leader in access control.

SPECIFICATION

MBK-ML600-D-MDS

- Aluminium housing
- Dual voltage 12/24 VDC @ 480/240mA x 2
- 280kgs (600lb) holding force x 2
- Built in surge protection
- Surface mount
- Fail safe operation (power to lock)
- +/- 15% voltage tolerance
- -10° to +50° operating temperature
- Push off release pin on armature

- Monitored (Lock Monitoring)
- Voltage free relay contacts
- Door Status Monitoring

(Lock monitoring checks maglock is reporting itself as locked, Door status monitoring has a contact that works independantly from Maglock, and shows if the door is open or closed)

DIMENSIONS

MBK-ML600-D-MDS

- 500x42x25 (mm) Maglock
- 180x38x13 (mm) Armature x 2
- 3.94kg Boxed
- 2.26kg Unboxed



FEATURES

MBK-ML600-D-MDS

- Fire rated (30, 60, 90 & 120 min timber door set)
- Slimline mini magnet
- Clean and compact design
- No residual magnetism
- Status LED indication on ML600-D-MDS

Suitable Brackets/Housings:

- BK600-D-ZL (Double ZL bracket)
- BK600-D-L (Double L Bracket)
- BK600-D-FL/AB (Architectural FL) x 2
- AB600ZL-DC (Architectural ZL) x 2
- AB600CL (Architectural L) x 2
- AH600 (Required for Fire Doors) x 2
- BK600U (Glass door bracket) x 2
- GD600ZL-AB (Glass Door ZL) x 2

CONTENTS

MBK-ML600-D-MDS

- Double slim line mini magnet (600lb)
- Armature plate x 2
- 600GB fixing kit x 2
- Instructions
- Armature fixing template

OTHER PRODUCTS

AH600



EBNT/TF1-PLUS



ML600



DU-CB/PTE

