

## Hand/Foot Operated Pneumatic Pad

Part No. **NC805P**



### Overview

- Ideal for people who find it difficult to press the buttons on standard tail call leads.
- Must be used in conjunction with a separately-available NC805AS Air Switch.
- Applying pressure to the pneumatic pad operates the highly-sensitive NC805AS air switch which in turn, when connected to a compatible call point's remote socket via its 6.35mm remote jack, triggers a Standard call.



### More Information

### Technical Specifications

|                           |                                                                                                                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility             | C-TEC's Quantec and 800 Series Call Systems. Must be used in conjunction with NC805AS Air Switch.                                                                                                |
| Quiescent current         | 0mA (none).                                                                                                                                                                                      |
| Alarm current             | Determined by the type of control equipment and number / type of field devices connected to the system.                                                                                          |
| Indicators                | Reassurance LED on host call point will illuminate steady when the host NC805AS Air Switch is activated and/or removed.                                                                          |
| Controls                  | Pneumatic Pressure Pad (applying sufficient pressure causes the host NC805AS Air Switch to activate and generate a Standard call if connected to a compatible Quantec or 800 Series call point). |
| Connections               | End of PVC tubing connects to spigot on end of NC806AS Air Switch.                                                                                                                               |
| Onboard Sounder           | No.                                                                                                                                                                                              |
| Onboard Infrared Receiver | No.                                                                                                                                                                                              |
| Product dimensions (mm)   | 95mm diameter x 20mm deep. PVC tubing measures 2m.                                                                                                                                               |
| Construction & finish     | PVC.                                                                                                                                                                                             |



IP Rating IP20.

Weight 118g

Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)

F 01942 829867 W [www.c-tec.com](http://www.c-tec.com)



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom