

**NIPNVR004A08PASL****4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD****ADVANCE
SERIE**

Network video recorder (NVR) for 4 IP channels (4 PoE), NDAA compliant, max. resolution 8 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 80 Mbps. Supports all DVA video analysis functions for the connected cameras. Number plate database.

Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. 48 V power supply unit included. This NVR connects to Comelit servers protected by AWS services.

AWARDS



NIPNVR004A08PASL

4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD

MAIN FEATURES

Video inputs	4 PoE (4K/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF)
Main video output	1 HDMI (4K) 1 VGA (1920x1080)
Audio Inputs/Outputs	1 / 1
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@8MP
Additional Hard Disks (SATA)	1 (10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Recording methods	Automatic, manual, programmed, event
Maximum number of channels being played simultaneously	1@4K, 6@Full HD
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, SNMP, ONVIF (Profile-T, Profile-S, Profile-G)
IP assignment	DHCP, manual
Max bandwidth (Mbps)	80
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	64
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function
Car plate database [max. number of registrable plates]	1000

FUNCTIONS

Motion detection	Yes
------------------	-----

HARDWARE SPECIFICATIONS

Type of connections/ports	1 x Ethernet 10/100/1000 Mbit/s, 2xUSB 2.0, 4 x Ethernet PoE 10/100 Mbit/s
---------------------------	--



NIPNVR004A08PASL

4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD

HARDWARE SPECIFICATIONS

Fanless Yes

Yes

GENERAL DATA

Machine absorption (no HDD) (W) 10

10

Maximum absorption per POE port (W) 30

30

POE total power (W) 48

48

Maximum distance in long range mode (CAT5e/CAT6) (m) 150

150

Power supply voltage (VDC) 48

48

Height (mm) 45

45

Width (mm) 300

300

Depth (mm) 249

249

Product weight (g) 2200

2200

Type of finishing materials Metallic

Metallic

Product color Black

Black

Operating temperature (°C) -10 ÷ 50

-10 ÷ 50

Operating humidity (RH max) (%) 25 ÷ 90

25 ÷ 90

Supplied accessories Power supply, Mouse

Power supply, Mouse