

**NIPNVR008N06PASL****8CH POE NVR, NEXT SERIES, NDAA, NO HDD****NEXT
SERIE**

Network video recorder (NVR) for 8 IP channels (8 PoE), NDAA compliant, max. resolution 6 MP, video compression H.265S / H.265+ / H.265 / H.264, dual streaming, bandwidth 64 Mbps. Supports all DVA video analysis functions for the connected cameras. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. 48 V power supply unit included. This NVR connects to Comelit servers protected by AWS services.

AWARDS



NIPNVR008N06PASL

8CH POE NVR, NEXT SERIES, NDAA, NO HDD

MAIN FEATURES

Video inputs	8 PoE (6MP/5MP/4MP/3MP/1080P/960P/720P/D1/CIF)
Main video output	1 (VGA), 1 (HDMI), 1920x1080
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@6MP
Additional Hard Disks (SATA)	1 (10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Recording methods	Automatic, manual, programmed, event
Maximum number of channels being played simultaneously	1@6MP, 4@Full HD
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, SNMP, ONVIF (Profile-T, Profile-S, Profile-G)
IP assignment	DHCP, manual
Max bandwidth (Mbps)	64
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	32
Main functions	Video analysis (only with dedicated cameras), Alarm system function

FUNCTIONS

Motion detection	Yes
------------------	-----

HARDWARE SPECIFICATIONS

Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 8 x Ethernet PoE 10/100 Mbit/s
Fanless	Yes

GENERAL DATA

Machine absorption (no HDD) (W)	5
---------------------------------	---



NIPNVR008N06PASL

8CH POE NVR, NEXT SERIES, NDAA, NO HDD

GENERAL DATA

Maximum absorption per POE port (W)	30
POE total power (W)	72
Maximum distance in long range mode (CAT5e/CAT6) (m)	150
Power supply voltage (VDC)	48
Height (mm)	42
Width (mm)	255
Depth (mm)	222
Product weight (g)	1.1
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse