

**NIPNVR016A12PBSL****16CH NVR, 12MP, POE, AI, NDAA, NO HDD****ADVANCE
SERIE**

Network video recorder (NVR) for 16 IP channels (16 PoE), NDAA compliant. Max. resolution 12 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 160 Mbps. Supports all DVA video analysis functions for the connected cameras. Face and number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Alarm inputs/outputs. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. This NVR connects to Comelit servers protected by AWS services.

AWARDS



NIPNVR016A12PBSL

16CH NVR, 12MP, POE, AI, NDAA, NO HDD

MAIN FEATURES

Video inputs	16 PoE (12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF)
Main video output	1 HDMI (4K) 1 VGA (1920x1080)., 1 (HDMI 1920x1080).
Audio Inputs/Outputs	1 / 1
Alarm Inputs/Outputs	16/4
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@8MP 20fps@12MP
Additional Hard Disks (SATA)	4 (4x10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Recording methods	Automatic, manual, programmed, event
Recording type	Dual streaming
Protocols supported	DHCP, HTTP, HTTPS, TCP/IP, ONVIF, SNMP
IP assignment	DHCP, manual
Max bandwidth (Mbps)	160
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Main functions	Video analysis (only with dedicated cameras)
Maximum number of users that can be created	32

FUNCTIONS

Motion detection	Yes
E-mail notification	Yes

HARDWARE SPECIFICATIONS

Type of connections/ports	2xUSB 2.0, 1xUSB 3.0, 16 x Ethernet PoE 10/100 Mbit/s, 2xEthernet 10/100 Mbit/s
---------------------------	---



NIPNVR016A12PBSL

16CH NVR, 12MP, POE, AI, NDAA, NO HDD

GENERAL DATA	
Machine absorption (no HDD) (W)	20
POE total power (W)	150
Supply voltage	100÷240, 50÷60Hz
Height (mm)	70
Width (mm)	440
Depth (mm)	390
Product weight (g)	4600
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse, Rack mounting brackets
System backup	USB 2.0