

**NIPNVR064A16NASL****64CH NVR, ADVANCE SERIES, NDAA, NO HDD****ADVANCE
SERIE**

Network video recorder (NVR) for 64 IP channels, NDAA compliant, max. resolution 16 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 640 Mbps. Supports all DVA video analysis functions for the connected cameras. Face and number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Alarm inputs/outputs. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. This NVR connects to Comelit servers protected by AWS services.

AWARDS



NIPNVR064A16NASL

64CH NVR, ADVANCE SERIES, NDAA, NO HDD

MAIN FEATURES

Video inputs	64 (16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF)
Main video output	1 HDMI (8K) 2 HDMI (4K) 1 HDMI (Full HD) 1 VGA
Audio Inputs/Outputs	1 / 1
Alarm Inputs/Outputs	24/8
Maximum load alarm outputs	12-24 V DC/AC 0,5A
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@16MP
Additional Hard Disks (SATA)	16 (16x10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Recording methods	Automatic, manual, programmed, event
	HDMI 1: 64, HDMI 2: 36, HDMI 3: 16, HDMI 4: 16
Maximum number of channels being played simultaneously	1@16MP, 4@4K
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, SNMP, ONVIF (Profile-T, Profile-S, Profile-G)
IP assignment	Manual, DHCP
Max bandwidth (Mbps)	640
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	64
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function, RAID (1, 5, 6, 10)
Car plate database [max. number of registrable plates]	50000



NIPNVR064A16NASL

64CH NVR, ADVANCE SERIES, NDAA, NO HDD

SOFTWARE/FIRMWARE SPECIFICATIONS

Face database [number of groups and faces]	32 groups 10,000 faces
--	------------------------

FUNCTIONS

Motion detection	Yes
------------------	-----

HARDWARE SPECIFICATIONS

Type of connections/ports	1xUSB 3.0, 2x eSATA, 2xEthernet 10/100/1000 Mbit/s, 3xUSB 2.0
---------------------------	---

GENERAL DATA

Machine absorption (no HDD) (W)	50
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	143
Width (mm)	437
Depth (mm)	483
Product weight (g)	13500
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Mouse, Rack mounting brackets