

Product Code: PA16622

Luckinslive 422572352

Description: Standard Analogue 24 hr Timer



General Information

Dimensions (mm)	72 x 94.5 x 53
Panel Dimensions (mm)	72 x 72
Display	Mechanical Dial
Timing Accuracy	1 Second / 24 Hour
Time Base	Quartz Crystal
Materials	Self-Extinguishing Thermoplastic
Mounting	Surface, Panel, or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Warranty (Years)	3

Programming

Programming Schedule	24 Hour
Available Operations	72 Operations
Switching Modes	ON and OFF
Minimum Interval (Between 2 Switchings)	20 Minutes
Switching Accuracy	1 Minute and 30 Seconds

Supply & Power

Supply Voltage (V AC)	230
Power Consumption (A)	0.5A
Cable Size (mm²)	1 - 6
IEC Protection Class	Class II When Installed According to Regulations

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-10 to +50

Features

Voltage Free 16A Changeover Contact
Suitable for Surface, Panel or Din Rail Mounting
Programming by 15 min Captive Segments
Manual Override with Automatic Return to Program
Contact Status Display

Outputs

Number of Outputs	1
Relay/Contact Type	SPDT
Output Relay Resistive Load Rating (A)	16
Output Relay Inductive Load Rating (A)	3
Total Switch Rating (Resistive)	250V AC, 16A
Maximum Incandescent Lamp Load Rating (W)	1000 @ 250V
Squirrel-Cage Motor Maximum Load Rating (W)	350 @ 250V
Voltage Free Inductive Load (cos = 0.6)	3A 250V

