




FRONT




BACK



END



SIDE



DESCRIPTION

Confirmable 4 Button PA
Grade 3—Environmental Class II
Normally Closed

VARIANTS

PA4W— White ABS
PA4S— Black ABS, Stainless Steel Fascia

ACTIVATION

Latch Selectable
4x Microswitch (ALARM)
1x Tactile switch (TAMPER)
1x Back tamper PCB snapoff
Reset key provided

KNOCKOUTS

4 (1 END, 1 BACK, 2 SIDE)

OVERALL DIMENSIONS

84mm X 65mm X 26mm

TEMPERATURE RANGE


-40 to +50 degrees Celsius

STANDARDS MET

EN50131-2-6:2008
PD6662:2017

POWER INPUT

12V DC Nominal




IMAGE



(PA4S Shown)

END



PCB LINK LABELS

OUTPUT B	OUTPUT A



KNIGHT
FIRE & SECURITY

Unit 84 Seawall Road Ind. Estate
Cardiff UK CF24 5TH
Tel: +44 (0) 2920 488 129
Fax: +44(0) 2920 489 132

Drawing #: PA4
Drawn: Gareth Carpenter
Date: 01/02/2020
Revision: 1

All dimensions in mm
Do not scale



© Knight Fire & Security Products Ltd
All cases of infringement will be pursued.