

Product Code: PSPSS

Luckinslive 434561377

Description: Electronic 7 Day Time Switch with Boost



General Information

|                                    |                               |
|------------------------------------|-------------------------------|
| Dimensions (mm)                    | 86 x 86 x 35                  |
| Flush Mounting Back Box Depth (mm) | 25                            |
| Colour                             | Silver                        |
| Display                            | LCD, Clear Indication Display |
| Materials                          | ABS                           |
| Mounting                           | Surface and Flush Mounting    |
| Warranty (Years)                   | 3                             |

Outputs

|                                         |      |
|-----------------------------------------|------|
| Number of Outputs                       | 1    |
| Relay/Contact Type                      | DPST |
| Relay Voltage - Maximum (AC)            | 240  |
| Output Relay Resistive Load Rating (A)  | 16   |
| Output Relay Capacitive Load Rating (A) | 2    |

Programming

|                            |                                                              |
|----------------------------|--------------------------------------------------------------|
| Programming Schedule       | 24 Hour, 5/2 Day & 7 Day                                     |
| Available Operations       | Up to 10 per Day                                             |
| Summer/Winter Time Change  | Yes (Automatic)                                              |
| Memory Reserve             | Permanent Reserve Setting                                    |
| Button Lock                | Yes                                                          |
| Selectable Boost Durations | 15 Minutes, 30 Minutes, 1 Hour, 2 Hours, 4 Hours, or 6 Hours |

Supply & Power

|                          |                         |
|--------------------------|-------------------------|
| Supply Voltage (V AC)    | 220 - 240               |
| Frequency (Hz)           | 50                      |
| Maximum Cable Size (mm²) | 2.5 (Flex), 4.0 (Fixed) |
| IEC Protection Class     | Class II                |

Environment

|                            |          |
|----------------------------|----------|
| Ingress Protection         | IP20     |
| Operating Temperature (°C) | 0 to +40 |
| Temperature Rating         | T40      |

Unit 7 Target Park, Shawbank Road,  
Lakeside, Redditch B98 8YN United Kingdom  
T: +44 (0)1527 515150 | F: +44 (0)1527 515143  
E: info@espuke.com | W: espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN