

Product Code: Q555.2110V

Luckinslive 405912816

Description: 110V Standard 4 Pin Time Switch, 2 On and Offs



General Information

Dimensions (mm)	146.5 x 105.7 x 82
Display	24 Hour Dial
Timing Accuracy	5 Minutes / Year
Time Base	Quartz Crystal
Mounting	Surface Mounting
Base Type	4 Pin
Warranty (Years)	5

Programming

Programming Schedule	24 Hour Program
Available Operations	2 ON/OFF Periods
Dial Calibration	15 Minute Divisions
Setting Accuracy	+/- 3 Minutes
Day Omission	Yes (omits the "ON" operation)
Temporary Override Facility (Manual Button)	Advance to "OFF", When Program "ON" and will Remain "OFF" Unit Next "ON" Operation and Vice Versa

Supply & Power

Supply Voltage (V AC)	110
Power Consumption (W)	0.6
Power Consumption (mA)	0.6W @ 230V
Cable Size (mm ²)	0.5 - 4
Power Reserve	100 Hours (Requires 300 hours to charge)
Battery Type	Rechargeable Ni-MH
IEC Protection Class	Class I (Must be Earthed)

Environment

Ingress Protection	IP20
Operating Temperature (°C)	0 to +50

Accessories

110469: FD930 Conduit Box Time Switch

Outputs

Number of Outputs	1
Relay/Contact Type	SPST
Relay Voltage - Maximum (AC)	110
Output Relay Resistive Load Rating (A)	20
Maximum LED Lamp Load Rating (W)	3600 @ 230V
Maximum Inductive Current Rating (A) (0.6pf)	5
Maximum Inductive Current Rating (A) (0.8pf)	12
Maximum Incandescent, Halogen Lamp Load Rating (W)	3600
Maximum Fluorescent Lamp Load Rating (W)	1980
Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W)	3600
Maximum Fluorescent Lamp Load Rating (W)	1980

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuke.com | W: espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN