

Quantec-Pro Monitoring Point

Part No. **QP904**



Overview

- A stylish monitoring point c/w reset button and isolation keyswitch for use on a Quantec-Pro addressable call system.
- Can generate a Standard or Emergency call when a fire exit or drug cupboard is opened (via magnetic contacts) or when a door bell rings.
- Can be used to monitor any device with a normally open or normally closed switch - ideal for interfacing PIRs, strip switches, flow switches and other devices to Quantec.
- Red/green reassurance LED.
- When isolated, the QP904's reassurance LED will illuminate Green and the monitored door or device may be opened and closed without signalling a call on the system.
- Surface mountable.



More Information

Quantec-Pro is C-TEC's next generation addressable call system. It keeps everything that is good about existing Quantec – stable protocol, ease of system set-up, optional Cloud based data monitoring – and enhances it with stylish devices, improved power efficiency, greater programming flexibility and more. The result – a powerful, aesthetically-pleasing call system that is perfect for use across the entire care sector.

Technical Specifications

Quiescent current 0.6mA.



Alarm current	12.4mA.
Indicators	Red/Green Reassurance LED (lit green when device is isolated).
Controls	Isolation keyswitch (switches monitoring off when ISOLATED); Reset button (cancels calls made from the monitoring point).
Connections	CONN2 (NET-; NET+, R/B; G; SW). CONN 1 (Doorbell input).
Expansion connections	R (Red) and G (Green) connections allow the connection of an optional dummy/extender overdoor light.
Onboard Infrared Receiver	No.
Product dimensions (mm)	120 W x 100 H x 39 D mm. Surface mounting.
Construction & finish	Polycarbonate RAL9003.
IP Rating	IP21.
Weight	150g
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.

