

## Infrared Patient Neck Pendant (push for call)

Part No. **QT432**



### Overview

- Allows patients in bedrooms and communal areas to remotely trigger standard calls via a Quantec infrared call point, ceiling receiver or radio receiver
- Alleviates the need for long, potentially hazardous tail call leads.
- Supplied with an anti-ligature neck lanyard.
- 10m line-of-sight IR transmitting range.
- Radio coverage dependent on the Quantec receiving device used.
- Powered by a user-replaceable 12V alkaline battery.
- Can be programmed with a unique User ID so staff can see who is calling using a QT423 configurator.
- Supplied with a sheet of coloured markable labels.



### Technical Specifications

|                           |                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility             | Compatible with C-TEC's Quantec call systems.                                                                                                |
| Type                      | Infrared/Radio.                                                                                                                              |
| Coverage                  | 10m line-of-sight infrared coverage (940nm modulated @ 38 Khz); 60m typical radio coverage dependent on environmental factors (RF868.3 MHz). |
| Max battery size and type | 12 Volt Type A23/23A (8LR50) alkaline (non-rechargeable). User replaceable.                                                                  |
| Indicators                | Confidence LED/battery status indicator.                                                                                                     |
| Controls                  | 1 x activation button (triggers a Standard call).                                                                                            |
| Product dimensions (mm)   | 47 W x 83 H x 16 D mm.                                                                                                                       |
| Construction & finish     | TBC.                                                                                                                                         |



|                                  |                                                                                                                                                 |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| IP Rating                        | IP41.                                                                                                                                           |
| Weight                           | 30g.                                                                                                                                            |
| Operating conditions/temperature | -5°C to +40°C. Max. relative humidity 95% non-condensing.                                                                                       |
| Notes                            | The transmitter's operation can be tailored to suit a specific site using a QT423 Configurator. Refer to the device's instructions for details. |

