

REKOR HD

Product Code: RHD4KB2G

Description: 4 Channel 500GB DVR with 2x 2MP Bullet Camera CCTV Wired Kit

Technical Specification Bullet Camera Kit

Luckinslive 425148136

ESP
ScolmoreGROUP



Component 1

4 Channel Full HD 500GB HDD DVR

Quantity

1

General Information

Dimensions (mm)	300 x 227 x 53
Materials	Steel - Body ABS - Faceplate

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	<10 (without hard disk)

Media Information

Display Video Output	1 x HDMI, 1 x VGA & 1 x BNC
Display Split	1 & 4
Display Resolutions	1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080, 1080x1440, 3840x2160
Sync Playback	4 Channel 1080P
Backup Mode	USB2.0 devices

System

Operating System	LINUX
------------------	-------

Recording

Internal HDD	500GB (1 x SATA)
Video/Audio Compression	H.265
Recording Resolution	1080P @15fps
Record Rate (Main Stream)	4 Channels @1080P
Recording Mode	Manual/Motion Detection/Schedule

Network

Network Connection	Ethernet (RJ45 10M/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP
Network Monitoring	CMS Windows & Mac, Android & iPhone apps
USB Interface	2 (1 Front & 1 Back)

Inputs & Outputs

Video Input Channels (BNC)	4
Audio Input Channels (RCA)	4
Audio Output Channels (RCA)	1

Environment

Operating Temperature (°C)	0 to +55
Relative Humidity Resistance (%)	10 to 90

Component 3

18.3M Cables With (RHD) Right Hand Down Connections

Quantity

2

Component 2

3.6mm Fixed Lens 2MP HD Bullet Camera

Quantity

2

General Information

Dimensions (mm)	Ø71 x 151
Colour	Grey
Sensor Size (")	1/2.8"
Lens size (mm)	3.6
Effective Pixels	NTSC/ PAL:1920(H) x 1080(V)
Maximum IR Distance (m)	30
Operating Voltage (V DC)	12
B&W Minimum Illumination (Lux)	0.05
Lens Type	Fixed
Viewing Angle (°)	87
Video Output	1Vpp, 75 ohms
Auto Gain Control	Auto
Ingress Protection	IP66
Operating Temperature (°C)	-30 to +55
Weight (Kg)	0.35

Component 4

DVR Power Supply Unit

Quantity

1

General Information

Dimensions (mm)	110 x 49 x 33
Colour	Black
Materials	ABS
Supply Voltage (V AC)	110 - 240
Number of Outputs	5
Output Rating	12VDC @ 5A

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN