

Roller Shutter Contact

Code: RS002/ALI/G2/B

RS007 Type B | Roller Shutter Contact | Grade 2 | Aluminium | Resisored



This roller shutter contact can be used in most security systems up to and including grade 1 & 2 as specified in EN50131-1:2006 and is compliant with EN50131-2-6:2008 and environmental class III. It operates as a normally closed circuit going open when the magnet housing is moved away from the contact housing. This contact can be used on roller shutter doors to detect the unauthorised entry of an intruder. The contact is sealed to prevent access to the inside.

Features & Benefits

- High Quality Alloy Finish
- Other resistor value available
- 45cm or 1 mtr Armoured cable lengths
- EN50131-2-6 Grade 2
- Environmental Class III



Security

EN50131-2-6 Grade	2
Tamper Protection	Internal

Environmental

EN50130-5 class	Class III
IP Rating	32
Temperature range	-10°C - +40°C

Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	170 x 50 x 12
Magnet Dimensions (mm)	80 x 71 x 30

Electrical

Connection type	Wired
No. of terminals	3 Wire
Contact type	Normally Closed
Contact Material	Ruthenium
Wire length (mm)	450

Features

Mode of operation	EOL/ FSL
Resistor Type	B
Operation Axes (X, Y, Z)	X, Y
Pull-in gap (X, Y, Z)mm	25, 50
Suitable for Double Door	Yes
Connection type	Wired
No. of terminals	3 Wire

Mechanical

Colour	Aluminium
--------	-----------