

SPECIFICATION SHEET




Email: sales@securiflex.co.uk | Website: www.securiflex.co.uk | Tel: 033 33 44 66 23



SFX/BS5308-PT1-TY1-2P-1.5-LSZH-D-BLK-U

BS5308 Part 1 Type 1 2 Pair 1.5mm LSZH Black CPR: Dca -s1 -a2 -d2

Import / Export Commodity Code 8544492000 / 85444920



Cable Construction

Overall Screen Quad x 1

Conductor

Annealed copper

Conductor cross sectional area (mm²)

1.5

Insulation

XLPE

Insulation Colour(s)

Black, Blue, Black, Green

Al-PET Shield

>=115%

Mylar Spiral

>=115%

Drain Wire

Drain Wire Conductor

Tinned Copper

Drain Wire Conductor cross sectional area (mm²)

0.5

Jacket

LSZH

Overall Diameter (mm)

8.50

Outer Jacket Colour

Black RAL 9005

Reaction to Fire

Dca -s1 -a2 -d2

Electrical Characteristics

Max Conductor DC resistance @ 20°C

12.1Ω/km

Rated Temperature (°C)

-40 to 90

Rated Voltage (V)

300/500V

Insulation Resistance @20°C

5000MΩ/km

Standards

PAS 5308-1

Application

Control and Instrumentation.



Every care is taken to ensure all information in this publication is correct. No legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information of this spacification without notice. E&OE.
Registered in England & Wales, Company No. 03758330. VAT number:7365084