

SPECIFICATION SHEET


Email: sales@securiflex.co.uk | Website: www.securiflex.co.uk | Tel: 033 33 44 66 23



SFX/BS5308-PT1-TY1-5P-0.75-LSZH-D-BLK-U

BS5308 Part 1 Type 1 5 Pair 0.75mm LSZH Black CPR: Dca -s1 -a2 -d2

Import / Export Commodity Code 8544492000 / 85444920



Cable Construction

Conductor	Annealed copper
Conductor cross sectional area (mm2)	0.75

Insulation

Insulation Colour(s)	Black, Blue, Black, Green, Blue, Green, Black, Brown, Blue, Brown
----------------------	---

Al-PET Shield	>=115%
---------------	--------

Mylar Spiral	>=115%
--------------	--------

Drain Wire

Drain Wire Conductor	Tinned Copper
Drain Wire Conductor cross sectional area (mm2)	0.5

Jacket

Overall Diameter (mm)	12.20
Outer Jacket Colour	Black RAL 9005
Reaction to Fire	Dca -s1 -a2 -d2

Electrical Characteristics

Max Conductor DC resistance @ 20°C	26Ω/km
Rated Temperature (°C)	-40 to 90
Rated Voltage (V)	300/500V
Insulation Resistance @20°C	5000MΩ/km
Standards	PAS 5308-1
Application	Control and Instrumentation.

