

SPECIFICATION SHEET




Email: sales@securiflex.co.uk | Website: www.securiflex.co.uk | Tel: 033 33 44 66 23



SFX/BS5308-PT1-TY1-5P-1.5-LSZH-D-BLK-U

BS5308 Part 1 Type 1 5 Pair 1.5mm LSZH Black CPR: Dca -s1 -a2 -d2

Import / Export Commodity Code 8544492000 / 85444920



Cable Construction

Conductor	Annealed copper
Conductor cross sectional area (mm ²)	1.5

Insulation

Insulation Colour(s)	Black, Blue, Black, Green, Blue, Green, Black, Brown, Blue, Brown
----------------------	---

Al-PET Shield

Mylar Spiral

Drain Wire

Drain Wire Conductor	Tinned Copper
Drain Wire Conductor cross sectional area (mm ²)	0.5

Jacket

Overall Diameter (mm)	
Outer Jacket Colour	Black RAL 9005
Reaction to Fire	Dca -s1 -a2 -d2

Electrical Characteristics

Max Conductor DC resistance @ 20°C	
Rated Temperature (°C)	-40 to 90
Rated Voltage (V)	300/500V
Insulation Resistance @20°C	5000MΩ/km
Standards	PAS 5308-1
Application	Control and Instrumentation.



Every care is taken to ensure all information in this publication is correct. No legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information of this specification without notice. E&OE.
Registered in England & Wales, Company No. 03758330. VAT number:7365084