



TITLE:

OSP Overall Foil Screened Pairs LSZH

CODE:



SFX/OSP2-LSZH-D-GRY-100

DESCRIPTION:

100m OSP2 2pr 24AWG Overall Foil
Screen 600V Grey LSZH (9502)

SUPPLIED AS:

Reel of 100m





Product Specification

Cable Construction

Cable Construction	2 Pairs
CPR	Dca -s:2 -a:1 -d:2
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8(0.20mm ²)
Overall Diameter (mm)	5.50 ±0.20

Insulation

Insulation	LSZH
Insulation Colour	Red,Black;White,Black
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.28

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Grey
Overall Diameter (mm)	5.50 ±0.20
Jacket Colour	Grey RAL 7042
Jacket Thickness (mm)	0.70

Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	<79.00O/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V





**BELDEN
EQUIVALENTS**



MORE INFORMATION:

Sorry, no more information is available for this product

Belden equivalents



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

FLAME-FLEX

Drum-Roll

LUCKINS

epim

ELECTRICAL
DISTRIBUTORS'
ASSOCIATION

BSI

KNX

cdi

CPR

UK
CA