

Datasheet

SL1-33 - Adjustable electronic cylinder kit


Product Description

The Smartloxx cylinder from CDVI is an intelligent, autonomous double-knob cylinder designed for maximum security and flexibility. Using innovative technology, it enables wireless, high security access control for Euro-profile locks – ideal for businesses, government institutions, and private users.

Its modular system allows extensions in 2.5 mm increments up to 30 mm, adapting flexibly to various door thicknesses.

Users choose between three authentication methods: MIFARE® DESFire® EV2/EV3 credentials, touch patterns from 4–14 digits (smartCode), and smartphone access. With memory for up to 3,000 credentials, the SL1 enables efficient access management for high security environments.

smartloxx
**PATENTED
BREVETÉ**



Key Features

- Fits directly onto the existing cylinder hole with no door adjustments needed
- 5-field touchcode and LED indicators
- Setup and unlocking via smartphone app
- Hold-open function for office/commercial use
- Time profiles for individual permissions
- Logging of the last 3,000 openings for complete traceability
- Kit includes: 1x cylinder, 1x battery, 2x HS-10



Certification



Certification



DEEE



Certification





IP65



-20°C to 70°C

Product Specifications


Material:	Stainless steel
Mounting:	Euro-profile cylinder slot
Technology:	MIFARE® DESFire® EV2/3, Bluetooth®
Frequency:	13.56MHz (RFID credential) 2.4GHz (smartphone App)
User code:	4–14 digits, 5-field touch code
Time delay:	4 to 60 seconds
Memory:	3,000 credentials (access-on-device)
Cycles tested:	35,000
Firmware updates:	Via 2.4 GHz wireless interface, prepared for 868 MHz
Weight:	350g (SL1-33)
Dimensions:	
• Outer knob:	Ø 30mm, (L) 40mm
• Inner knob:	Ø 30mm, (L) 31mm
• Total length:	148mm (SL1-33)



Electrical Specifications

Power supply:	3V CR2 lithium battery (included)
Battery life:	Up to 35,000 openings or 2 years standby

Accessories




HS-20, HS-30

Half-shells for door length adjustment, 20-30mm



METALD

MIFARE® DESFire® EV2 tag credential (pack of 10)



BCD

MIFARE® DESFire® EV2 card credential (pack of 10)

Download the app!



AVAILABLE ON
Google Play

KEYLOXX

AVAILABLE ON
App Store

SMARTLOXX