



Network

SLA-T4680DSA

Doorjamb camera for PNM-9000QB, XNB-6002



Key Features

- Compatible with XNB-6001 not included
- 2 Megapixel (1920 x 1080) resolution
- 4.6mm pinhole lens
- 0.06Lux@F2.5
- 8m cable
- Easy installation
- Flexible panning -30° to 30°
- Multiple housing color options to match the door jamb
- Hidden security screw for discrete look
- Includes lens & housing

Compatible Accessories (Optional)



XNB-6001



XNB-6002



PNM-9000QB

SLA-T4680DSA

Doorjamb camera for PNM-9000QB,
XNB-6002



Specifications

Video	
Imaging Device	1/2.8" 2M CMOS
Min. Illumination	Color: 0.06Lux(F2.5) BW: 0.06Lux(F2.5) * with PNM-9000QB, XNB-6002, PNM-C16000QB
Lens	
Focal Length (Zoom Ratio)	4.6mm fixed focal
Max. Aperture Ratio	F2.5
Angular Field of View	H: 73° / V: 39° / D: 85°
Min. Object Distance	0.3m(0.98ft)
Focus Control	Fixed
Mount Type	RJ12 connected with main unit
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	Flexible panning -30°~30°
Environmental & Electrical	
Operating Temperature / Humidity	-10°C~+55°C(+14°F~+131°F) / 0~90% RH
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH
Mechanical	
Color / Material	Housing: Silver / Plastic Lens: Black / Plastic, Aluminum
Product Dimensions / Weight	Housing: 42.9(W)x33.0(H)x170.0(D)mm(1.69"x1.30"x6.69"), 70g(0.15lb) Lens: 30(W)x27.9(H)x45(D)mm(1.18"x1.10"x1.77"), 41g(0.09lb) Cable: 8m(26.2ft)

SLA-T4680DSA

SLA-T4680DSA

Doorjamb camera for PNM-9000QB,
XNB-6002



CAD

Unit:mm [inch]

