

SMB-3

DIN Module Enclosure

Features

- ▶ Designed to house up to 4 Hochiki DIN Modules
- ▶ Quick-release screws
- ▶ Polyurethane gasket provides IP66 protection
- ▶ Corrosion free, resistant to most alkaline and acid
- ▶ Temperature resistance to +70°C, Impact resistant, and Non-flammable
- ▶ 20 knock-outs
- ▶ Supplied with DIN Rail and fixings.



Fitted enclosure as example

Description

Model SMB-3 is from a range of IP66 rated, grey (RAL7035) enclosures, designed for use with the Hochiki range of DIN Modules. The SMB-3 features a selection of metric knockouts and is supplied with a transparent black lid as standard; an opaque lid is also available (sold separately).

The unit is supplied with a DIN Rail section (plus fixings) and will accept up to four Hochiki DIN Rail Modules, side-by-side.

Specification			
Ordering codes	SMB-3 - Base and transparent lid		SMB-3(LID) - Opaque lid
IP rating	IP66		n/a
Colour	Box - Grey (RAL7035) Lid - Transparent black		Grey (RAL7035)
Material	Box - Polystyrene Lid - Polycarbonate		Polystyrene
Weight (g)	575		300
Dimensions (mm) DIN Dimensions (mm)	L 180 x W 110 x H 165 L 100 x W 35 (*top hat)		L 180 x W 110 x H 92 n/a
Knock-out configuration	Long sides	1 x M32/40 4 x M20	n/a
	Short sides	1 x M32/40 4 x M20	
Suitable protection against	Weak alkali, strong alkali, alcohol, petrol, benzene, mineral oil, diesel, ammonia, vegetable oil, animal oil		

FASTENER INFORMATION:	For Mounting plate (always required) - 4 x M3 CTSK Self Tapper	For CHQ Module PCB - 2 x M4 Pan Head Screws + 2 split washers	For 'mini' CHQ - 2 x M3 CTSK Machine Screws	For DIN Rail washers - 2 x M3 Pan Head Machine Screws + 2 splits
-----------------------	--	---	---	--

