

Product Code: UDTAKITSS

Luckinslive 405575839

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit



Component 1 Description		Quantity	Component 2 Description		Quantity
UDTAPCMSS - Pull Cord Module		1	UDTAPLBMSS - Power, Light and Buzzer Module		1
General Information			General Information		
Dimensions (mm)	87 x 87 x 41		Dimensions (mm)	87 x 87 x 41	
Colour	Grey		Plate Size	Single Gang	
Pull Cord Length (m)	3 (Including 2 Triangular Bangles)		Colour	Grey	
Plate Size	Single Gang		Materials	Stainless Steel (Grade 304)	
Materials	Stainless Steel (Grade 304)		Mounting	Surface or Flush (Surface Box Not Included)	
Mounting	Surface or Flush (Surface Box Not Included)		Indication	LED illuminates in red when in alarm state	
Anti-Ligature	Yes		Activated Buzzer Sound Level (db)	>80	
Supply & Power			Purpose	Activation and Reset Circuits	
Operating Voltage (V DC)	12		Maximum Cable Size (mm²)	1.5	
Maximum Cable Size (mm²)	1.5		Power Consumption (A)	0.2	
Power Consumption (W)	0.3		Battery Backup	A23 Battery	
Environment			Input Type	Ground & 2 live circuits - X1 & X2	
Ingress Protection	IP20		Activation Type	Energise with a Normally Open Clean Contact	
Operating Temperature (°C)	-10 to +40		Output Type	1 Switched Live sharing common ground Separate output for additional sounders	
			Number of Outputs	2	
			Output Rating	12V 500mA	
			Ingress Protection	IP20	
			Operating Temperature (°C)	-10 to +40	

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN

Product Code: UDTAKITSS

Luckinslive 405575839

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit

Component 3 Description	Quantity
UDTAREMSS - Assistance Alarm Reset Module	1
General Information	
Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Colour	Grey
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Box Not Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Operating Voltage (V DC)	12
Maximum Cable Size (mm²)	1.5
Power Consumption (W)	0.9
Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40

Warranty Years	2
----------------	---

Additional Information	If mounting surface you will need UDTASMBSS Surface Mount Back Box.
------------------------	---

Features	Accessories
Anti-Ligature Red Pull Cord	UDTAPLBMSS: Stainless Steel Assistance Alarm, Power, Light and Buzzer Module UDTALBMSS: Stainless Steel Assistance Alarm Light and Buzzer Module UDTAPCMSS: Stainless Steel Assistance Alarm Pull Cord Module UDTASPCSS: Stainless Steel Assistance Alarm Replacement Pull Cord UDTAREMSS: Stainless Steel Assistance Alarm Reset Module UDTASMBSS: Stainless Steel Surface mount Box