

BEACON

Technical Specification



Product Code: UDTAPLBMSS

Luckinslive 405575868

Description: Assistance Alarm, Power, Light and Buzzer Module



General Information

Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Colour	Grey
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Back Box Not Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Purpose	Activation and Reset Circuits
Warranty (Years)	2

Supply & Power

Operating Voltage (V AC)	100 - 230
Maximum Cable Size (mm ²)	1.5
Power Consumption (A)	0.2
Battery Backup	Yes

Inputs

Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact

Outputs

Number of Outputs	2
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Output Rating	12V 500mA

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40

Supplied User Manual

Additional Information If mounting surface you will need UDTASMBSS Surface Mount Back Box.

Features

Built in Battery Backup with Supplied A23 Battery, Sounder Buzzes Intermittantly When Battery Needs Replacing.

Accessories

UDTAPLBMSS: Stainless Steel Assistance Alarm, Power, Light and Buzzer Module
UDTALBMSS: Stainless Steel Assistance Alarm Light and Buzzer Module
UDTAPCMSS: Stainless Steel Assistance Alarm Pull Cord Module
UDTASPCSS: Stainless Steel Assistance Alarm Replacement Pull Cord
UDTAREMSS: Stainless Steel Assistance Alarm Reset Module
UDTASMBSS: Stainless Steel Surface mount Box

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN



DoC



Installation



Quick Start



CLICK OR SCAN