

60m HDMI Extender WBXHDME6IR



HDMI Extender with IR playback 60m.
The extender uses single Cat-5e or Cat- 6 (recommended) cables instead of HDMI cable to transmit high definition signal upto 60m cutting down the cost. Designed for long distance transmission of high definition signal.

Special Features

- Support HDMI 1.4a
- Support 3D
- Support highest video resolution 1080p/60Hz
- Support
- 1.65Gbps data rate and tmds clock up to 165MHz
- Support 8/10/12 bit deep color
- Support AWG26 HDMI standard cable, input up to 15m, output up to 20m
- Signal transmission: By using single cat-5e or cat-6(recommended) cable instead of HDMI Cable it can extend the distance up to 60m between TX and RX.
- No loss of quality
- Needs 5V/1A power supply

BOX DIMENSIONS:

PART#: WBXHDME6IR

UPC: 840049304130

LENGTH: 81mm

WIDTH: 43mm

HEIGHT: 22mm

WEIGHT: 100kg

WARRANTY: 36 mths

For more information please
contact your ADI salesperson or
visit us at www.adiglobal.com

AVARRO™

60m HDMI EXTENDER WBXHDME6IR



HDMI Extender with IR playback 60m.
The extender uses single Cat-5e or Cat- 6 (recommended) cables instead of HDMI cable to transmit high definition signal upto 60m cutting down the cost. Designed for long distance transmission of high definition signal.

HDMI Input: 24/50/60fs/1080p/1080i/720P//576p/576i/480P/480i

Support Audio Input: DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD

HDMI Output: 24/50/60fs/1080p/1080i/720P//576p/576i/480P/480i

Support Audio Output: DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD

Max bandwidth: 165MHz

Max baud rate: 1.65Gbps

Input video signal: 0.5-1.5 Volts pp

Output DDC signal: 5Volts p-p (TTL)

Temperature: -15 degree to +55 degree

Using humidity: 5% to 90% RH (no condensation)

TX Max working current: 510mA

RX Max working current: 100mA

For more information please contact
your ADI sales person or visit us at
www.adiglobal.com

