

**WCW99****WALL-MOUNTED SOUNDER BEACON, IP21**

High-efficiency audio-visual signaller with low consumption, designed for fire alarm and surface-mounted systems. Has 32 main tones and 32 alternative tones, option of 2 different volume levels and 2 levels of optical coverage. Sound power at high volume 100 dB (A) @ 1 m. Absorption 14.5 mA (high volume and coverage), 12.5 mA (low volume and coverage). Optical coverage (W) 4 m x 9 m with low-consumption white flashing LED. Synchronised flashing lights for connection with several devices. Power supply 9-60 Vdc. IP21 protection rating. Dimensions (H x W x L) 45x109x120 mm. Approved to EN 54-3 and EN 54-23.



WCW99

WALL-MOUNTED SOUNDER BEACON, IP21

MAIN FEATURES

Number of tones available (n°)	32
EN regulations	EN54-3, EN54-23

HARDWARE SPECIFICATIONS

Type of finishing materials	ABS - V0 + Polycarbonate
Product color	Red
Visual indication	Yes
Coverage	(W) 4 x 9m
Visual indication colour	White
Synchronized flashing	Yes
Cross-section for terminals (mm)	0.5 ÷ 2.5
Operating temperature (°C)	-10 ÷ 55
Operating humidity (RH max @40°C) (%)	0 ÷ 95
Width (mm)	120
Height (mm)	109
Depth (mm)	45
Product weight (g)	232

ELECTRICAL SPECIFICATIONS

Supply voltage	9-60 VDC
Maximum absorption (mA)	14.5
Audible indication high level (dB@1m) (dB)	100

GENERAL DATA

IP protection rating	IP21
----------------------	------