



WMS99

WALL-MOUNTED SOUNDER, IP21



High performance audio signaller with low consumption, designed for fire alarm and surface-mounted systems. Has 32 main tones and 32 alternative tones, option of 4 different volume levels. Sound power at high volume 105 dB (A) @ 1 m. Absorption 4 mA / 2.3 mA / 1.3 mA / 1 mA (high / medium-high / medium-low / low volume). Power supply 9-60 Vdc. IP21 protection rating. Dimensions (H x W x L) 45x109x120 mm. Approved to EN 54-3.



WMS99

WALL-MOUNTED SOUNDER, IP21

MAIN FEATURES

Number of tones available (n°)	32
EN regulations	EN54-3

HARDWARE SPECIFICATIONS

IP protection rating	IP21
Type of finishing materials	ABS
Product color	Red
Cross-section for terminals (mm)	0.5 ÷ 2.5
Operating temperature (°C)	-10 ÷ 55
Operating humidity (RH max @40°C) (%)	0 ÷ 95
Width (mm)	120
Height (mm)	109
Depth (mm)	45
Product weight (g)	190

ELECTRICAL SPECIFICATIONS

Supply voltage	9-60 VDC
Audible indication high level (dB@1m) (dB)	105
Maximum absorption (mA)	4