

ZFP Touchscreen Control Module, CAST protocol

Part No. **Z41/CA**



Overview

- Supplied as standard in all pre-built ZFP CAST panels and all core ZFP CAST panels.
- Includes a user-friendly full-colour 4.3 inch 480 x 272 pixel LCD touchscreen.
- Separate distinct LEDs for mandatory EN54 indications plus five spare engineer programmable LEDs.
- Keyswitch or dynamic touchscreen button access to AL2 (Authorised User Level).
- Digital QWERTY keyboard.
- Touchscreen can be customised to include a company logo (.gif)
- Galvanically isolated USB port (for system programming).
- Indicator naming template (Microsoft Word format) downloadable from the Documentation tab below.



Technical Specifications

Compatibility	One required per ZFP standard, medium or large panel (supplied as standard on all pre-built ZFP CAST panels and all core ZFP CAST panels).
Protocol/compatibility	CAST.
Indicators	Full-colour 480 x 272 pixel touchscreen; 16 LEDS (11 reserved for mandatory EN54 indicators plus 5 engineer programmable indicators).
Controls	Interactive touchscreen with menu sensitive buttons; 1 x keyswitch allowing direct access to Access Level 2. Keyswitch requires S-KEY fire panel key.
Product dimensions (mm)	180 W x 170 H x 20 D mm.
Construction & finish	Plastic.



Weight TBC.
Operating conditions/temperature -5°C to +40°C. Max relative humidity: 95%.

