Auxiliary Device Isolator

Part No. BF367



Overview

- Allows a +24 VDC output from a fire alarm control panel to be remotely isolated to prevent autodiallers, water sprinklers, rollershutters, etc., from activating.
- Designed so that if monitoring is used on the +24 VDC output being controlled, a fault condition will show at the fire panel when the device is Isolated.
- Label includes a white ‘write on’ area allowing installers to add equipment locations.
- Fits on standard UK 25mm flush or surface mount back boxes.

CE

Technical Specifications

Activation current	10mA @ 27.6 VDC required to illuminate the amber Isolated LED
Indicators	Isolated LED.
Connections	OV; SW In; SW Out.
Product dimensions (mm)	85 W x 85 H x D 19mm.
Construction & finish	White PVC plate; Grey label; Silver plated brass switch material.
IP Rating	IP40.
Weight	TBC.
Operating conditions/temperature	-10ºC to +60ºC.
Notes	Switching Resistive load 3A @ 30V DC; Switching Inductive load 1.5A @ 30V DC; Non-switching current rating 5A Absolute Max.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com

You’re Safe with C-TEC

A PROUD BRITISH MANUFACTURER