ActiV Conventional Hi-Output W-2.75-9 Wall VAD c/w 100dB(A) Sounder (shallow base)

Part No. BF433C/CC/SR



Overview

- Third-party certified to EN54-3 (Sounders) and EN54-23 (VADs).
- Provides 'W-2.75-9' rated light distribution when wall mounted (min. 0.4 lux over a 2.75 x 9m cuboid area). Also rated as a W-4-4 VAD.
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low).
- Three selectable VAD flash rates (0.5Hz, 1Hz, OFF).
- Max. Alarm Current at 30Vdc = 20mA (Max. volume/0.5Hz flash).
- Typical Alarm Current at 30Vdc = 10mA (Max. volume/0.5Hz flash).
- IP21C rated.
- Manufactured in the UK by C-TEC.

Technical Specifications

Approvals/certifications	Certified to EN54-3 & 23 by the LPCB
Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Indoor areas only.
VAD category & coverage	W-2.75-9 rated light distribution (min. 0.4 lux over a 2.7.5m x 9m cuboid area). Also certified as a W-4-4 rated VAD.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com
You're Safe with C-TEC

Flash rate & colour	0.5Hz; 1Hz or OFF / White.
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	100dB(A).
Alarm current	Max. @ 30Vdc = 20mA; Typ. @ 30Vdc = 10mA (Max volume/0.5Hz flash).
Product dimensions (mm)	108mm diameter x 99mm deep
IP Rating	IP21C (Type A).
Weight	230g.
Operating conditions/temperature	-10ºC to +55ºC. Max. 95% RH (Non-condensing).