Addressable Overdoor Light c/w Sounder

Part No. QT606A



Overview

- An addressable overdoor light & sounder designed to increase call indication levels in large Quantec sites.
- Can be programmed to illuminate and sound when certain groups of call points are calling.
- Ideal for providing area indication or ‘follow me’ lights at the ends of corridors, etc
- Flash and sounder rates change/intensify to reflect the urgency of incoming calls.
- Adjustable volume control.
- Dual red and green LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Finished in tough, durable ABS plastic.

Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network)
Quiescent current	Less than 1.5mA.
Alarm current	40mA.
Indicators	Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call).
Controls	Adjust volume; Disable sounder.
Connections	R (Red); G (Green); Net +; Net –
Onboard Sounder	Yes. (Sound sequence changes and intensifies to reflect the urgency of the incoming call).
Onboard Infrared Receiver	No.
Product dimensions (mm)	86 W x 86 H x 48 D mm. Mounts on a UK 25mm single gang back box.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com

You’re Safe with C-TEC

Construction & finish	Plastic.
IP Rating	IP41.
Weight	58g
Operating conditions/temperature	-5ºC to +40ºC. Max. relative humidity 95% non-condensing.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com

You're Safe with C-TEC