1256

ACTUATOR RELAY. SIMPLEBUS 1 AND 2



Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.

1256

ACTUATOR RELAY. SIMPLEBUS 1 AND 2

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes

ELECTRICAL CHARACTERISTICS	
Type of power supply	External power supply
Power supply	12VAC/20VDC
Absorption (W)	0.6

HARDWARE FEATURES	
Number of outputs (n°)	1
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC)

GENERAL FEATURES	
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of finishing materials	ABS
Product color	White RAL9010
Depth (mm)	85
Height (mm)	35
Width (mm)	66

MAIN FEATURES	
Operating temperature (°C)	-10 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

The technical specifications are subject to change without prior notice.

1256

ACTUATOR RELAY. SIMPLEBUS 1 AND 2

MAIN FEATURES	
DIN rail mounted	Yes
DIN modules (no.) (n°)	4

The technical specifications are subject to change without prior notice.