41IOM000/240

ADDRESSABLE MODULE, 1 RELAY OUTPUT, 240VAC



Addressable module 41IOM000/240, with integrated on-board isolator, provides a voltage-free relay output for control of devices with supply voltage of 250Vac (4A) or 30Vdc (3A). Powered from the loop and controlled from the control panel via the communication protocol. The module is supplied in a plastic enclosure suitable for wall-mounting, with a clear cover to allow easy visual inspection. Approved to EN54-17 and EN 54-18.

41IOM000/240

ADDRESSABLE MODULE, 1 RELAY OUTPUT, 240VAC

MAIN FEATURES	
Isolator	Yes
EN regulations	EN54-17, EN54-18

HARDWARE SPECIFICATIONS	
Height (mm)	142
Width (mm)	80
Depth (mm)	45
Type of finishing materials	ABS
Product color	Branco, cobertura transparente
Product weight (g)	230
Operating temperature (°C)	-10 ÷ 60
Operating humidity (RH max @40°C) (%)	0 ÷ 96
Cross-section for terminals (mm)	0.4 ÷ 2.5

ELECTRICAL SPECIFICATIONS	
Supply voltage	15÷32VDC
Absorption in stand-by (mA)	0.18
Rated absorption	220µA@27VDC
Absorption with 1 LED ON (mA)	4
Output(s) maximum current	4A@250VAC / 3A@30VDC
Number of relay outputs (n°)	1

GENERAL DATA	
IP protection rating	IP21

The technical specifications are subject to change without prior notice.