41IOM000/240XL

ADDRESSABLE MODULE 1 RELAY OUTPUT 240VAC, LARGE BOX



Addressed module art. 41IOM000/240XL, with built-in isolator, controls a relay with voltage-free contact for controlling devices with power supply voltage up to 250 VAC (4A) or 30 VDC (3A). It is powered from the loop and controlled from the control panel by means of the communication protocol. This module is supplied in a plastic container suitable for surface mounting, with increased dimensions to make input and output wiring easier. Box dimensions (mm) 178 x 128 x 58. IP55 protection rating. Approved to EN54-17 and EN 54-18

41IOM000/240XL

ADDRESSABLE MODULE 1 RELAY OUTPUT 240VAC, LARGE BOX

Isolator	Yes
EN regulations	EN54-17, EN54-18

HARDWARE SPECIFICATIONS

Type of finishing materials	PS
Product color	Grey
Product weight (g)	320
Operating temperature (°C)	-10 ÷ 60
Operating humidity (RH max @40°C) (%)	0 ÷ 96
Cross-section for terminals (mm)	0.4 ÷ 2.0

ELECTRICAL SPECIFICATIONS

Supply voltage	15÷32VDC
Absorption in stand-by (mA)	0.18
Rated absorption	220µA@27VDC
Absorption with 1 LED ON (mA)	4
Output(s) maximum current	4A@250VAC / 3A@30VDC
Number of relay outputs (n°)	1

GENERAL DATA

IP protection rating	IP55

The technical specifications are subject to change without prior notice.