41IOM004XL

ADDRESSABLE MODULE WITH 4 RELAY OUTPUTS, LARGE BOX



Addressed module 41IOM004XL, with integrated on-board isolator, controls four relay outputs. It is powered from the loop and is controlled by the control panel by means of the communication protocol. This module is supplied in a plastic container suitable for surface mounting, with increased dimensions to make input and output wiring easier. Box dimensions (mm) 178 x 128 x 58. IP55 protection rating. Approved to EN 54-17 and EN 54-18

41IOM004XL

ADDRESSABLE MODULE WITH 4 RELAY OUTPUTS, LARGE BOX

Isolator	Yes
EN regulations	EN54-17, EN54-18

HARDWARE SPECIFICATIONS

Height (mm)	176
Width (mm)	126
Depth (mm)	57
Type of finishing materials	PS
Product color	Grey
Product weight (g)	320
Operating temperature (°C)	-10 ÷ 60
Operating humidity (RH max @40°C) (%)	0 ÷ 96
Cross-section for terminals (mm)	0.4 ÷ 2.0

ELECTRICAL SPECIFICATIONS

Supply voltage	15÷32VDC
Absorption in stand-by (mA)	0.18
Rated absorption	200uA@27VDC
Absorption with 1 LED ON (mA)	4
Output(s) maximum current	1A@30VDC/0.5A@125VAC
Number of relay outputs (n°)	4

GENERAL DATA

IP protection rating	IP55

The technical specifications are subject to change without prior notice.