41PAM000

ADDRESSABLE MANUAL CALL POINT



Addressable manual call point with built-in isolator. The button is equipped with a resettable special plastic key element (supplied) and sends an alarm signal to the control panel when it is activated by pressing the indicated point. It is equipped with an LED for signalling the alarm or test status. Wall mounting. Red ABS container. Approved to EN 54-11 and EN 54-17.

41PAM000

ADDRESSABLE MANUAL CALL POINT

HARDWARE SPECIFICATIONS	
Fragile element type	Resettable
Isolator	Yes
IP protection rating	
Type of finishing materials	ABS
Product color	Red
Width (mm)	90
Height (mm)	90
Depth (mm)	56

TECHNICAL CHARACTERISTICS	
Operating humidity (RH max @40°C) (%)	0 ÷ 96
Operating temperature (°C)	-10 ÷ 60

ELECTRICAL SPECIFICATIONS	
Operating voltage	15÷32 (27 VDC Nominal)
Current consumed in alarm status	3
Consumption during communication	160uA@27VDC

GENERAL DATA	
Type of detection point	Manual alarm button
EN regulations	EN54-11, EN54-17
Cross-section for terminals (mm)	0.4 ÷ 2.5
Product weight (g)	175

The technical specifications are subject to change without prior notice.