6721W/BM

MINI HANDSFREE BM MONITOR, S2



Wall-mounted hands-free monitor with full-duplex audio and 4.3" 16/9 colour screen and hearing induction loop. Allows colour and contrast control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 5 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Option of adding 3 additional buttons with accessory Art. 6734W. Complete with 2 x 8-position DIP-SWITCH for user code programming and button programming. The monitor can only be used in 2-wire Simplebus2 Colour systems. 115x160x22mm. Backplate art. 6710 is not supplied, and is available to purchase separately.

AWARDS

6721W/BM

MINI HANDSFREE BM MONITOR, S2

GENERAL DATA	
Height (mm)	160
Width (mm)	115
Depth (mm)	22
Product weight (g)	500
Product color	White RAL9003
Type of finishing materials	ABS
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY	
Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272

AUDIO FEATURES	
Induction loop function	Yes
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 40 Ohm, 1W

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Absorption in stand-by (W)	0.05

The technical specifications are subject to change without prior notice.

6721W/BM

MINI HANDSFREE BM MONITOR, S2

ELECTRICAL CHARACTERISTICS	
Maximum absorption (W)	8.8

HARDWARE FEATURES	
Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (5 with accessory art. 6734W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS	
Loudspeaker volume	Yes
Microphone volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes
Screen colour	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I (B1)
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES	
Door opener	Yes
Automatic door opening on call (Doctor)	Yes
Silent mode (Privacy)	Yes

The technical specifications are subject to change without prior notice.

6721W/BM

MINI HANDSFREE BM MONITOR, S2

GENERAL FEATURES	
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Outside door call input	Yes
Customisable ringtone	Yes
Automatic answer (handsfree)	Yes
Sending alarm calls	Yes
Actuator control	Yes
Multiple address	Yes
Door open signaling	Yes

The technical specifications are subject to change without prior notice.

6721W/BM

MINI HANDSFREE BM MONITOR, S2

ACCESSORIES



6711WV **ADAPTER PLATE FOR MINI HANDSFREE**

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6732A **DESK BASE FOR HANDS-FREE MINI MONITOR. S2**

Desk base installation accessory for hands-free Mini monitor in Simplebus 2 system.

6720 **Access. cables external passage for MINI HF. S2**

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.

6734W **ADD. BUTTONS KIT HANDS-FREE MINI MONITOR, WHITE**

Accessory for conversion of the monitors of the Mini series Art 6721W and 6721W/BM into 8-button versions. Includes an 8-button faceplate and an electronic module for button activation, which can be installed quickly without the need to open the monitor casing.

6710 **BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR**

Wall-mounting or residential series box backplate for MINI monitor, /BM versions with handset featuring magnetic induction for hearing aid wearers. Also includes riser distribution terminal Art. 1214/2C. Dimensions 145x100x4 mm.

The technical specifications are subject to change without prior notice.