IX0101CO

SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM



ViP | SIMPLEBUS2 | BUILDING KIT | SIMPLEBUS1 | AUDIO/VIDEO KIT

Front plate for Switch entrance panel in 2.5 mm thick brushed AISI 316 stainless steel, designed to house SimpleKey or third-party access control readers. Adapter art. 1250U (supplied) offers the option of using the audio or audio/video module (not supplied), depending on the type of wiring applied (Simplebus digital 2-wire or ViP). Complete with 1 pre-fitted, pre-wired button. White LED nameplate backlighting. IK08 protection rating. To be finished with flush-mounted box or surface-mounted casing. Panel dimensions: (L x H): 150x262.7 mm. Hole dimensions: 40x40 mm.

AWARDS

DESIGN MILANO

IX0101CO

SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM

GENERAL DATA	
Type	Monoblock
Height (mm)	262.7
Width (mm)	150
Depth (mm)	2.5
Product color	Steel
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.1621, Art.1622, Art.1622VC, Art.4680C, Art.4681
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	White

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08

The technical specifications are subject to change without prior notice.

IX0101CO

SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III

The technical specifications are subject to change without prior notice.