GDX Vandal Range

Readers—LF

GDX LF Readers

The GDX Vandal Resistant Reader is designed to work in the most demanding of operating environments which is ideal for internal or external installations.

- Standalone vandal resistant readers available for non-audio doors
- Up to 1,000 user fobs per reader
- Can utilise PAC format credentials
- Up to 10 mm fob read range
- Available as secondary version for read-in / read-out operation



Flush mount
(requires 45 mm wall recess)



Surface mount

Part Number(s)	**RDRRF-021** LF Flush mount	**RDRRF-022** LF Surface mount
Supported ID Device Formats	PAC	
Audio / Visual Indicators	Valid Fob: long 'bleep' sounds and Red/Green LED illuminates Invalid Fob: short 'bleep' sounds and Red/Green LED illuminates	
RFid Frequency	Low Frequency (153.6kHz)	
Maximum Read Range	10 mm / 0.394 in.	
Tamper Output	Certified to EN 50131-1 and EN 50131-3	
Recommended Cabling	6-core 24 AWG alarm cable (unscreened)	
Power input(s)	12–24V DC, <100mA @ 12V DC	
Dimensions (mm / in.)	107 (w) × 185 (h) × 35 (d) mm	101 (w) × 158 (h) × 27 (d) mm
Weight	0.62kg	0.74kg
Material	High Grade Stainless Steel	
Operating Temperature (°C / °F)	-40°C to +66°C	
Operating Humidity	10% to 85% Relative Humidity	
Warranty	5 years against electronic failure	
Compliance	CE, UKCA	

pacgdxcustomerservice@comelit-pac.co.uk
+44 (0) 161 406 3400 • www.pacgdx.com