
Xnightsbridge

DATASHEET



BATS4230V 4ft 22W LED Batten- 4000K

www.mlaccessories.co.uk



MLA PART CODE	BATS4
DESCRIPTION	230V 4ft 22W LED Batten- 4000K
NET WEIGHT (KG)	1.28
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	22
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2625
LUMENS LIGHT SOURCE ONLY (LM)	3370
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	147.56
CIRCUIT WATTAGE (W)	22.85
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.103
DISPLACEMENT FACTOR	>0.9
SVM	0.841
PST-LM	0.038
BEAM ANGLE (DEGREES)	115
LIFE SPAN (HRS)	50,000





Xnightsbridge

L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 20W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 480mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 88.56 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832993155
Data Croated: 27/02/2025 12:27	

Date Created: 27/02/2025 12:27





