

DATASHEET



CU6RCD

13A RCD Fused Spur Unit (Type A) - 30mA

www.mlaccessories.co.uk

| | |
|--|--|
| MLA PART CODE | CU6RCD |
| DESCRIPTION | 13A RCD Fused Spur Unit (Type A) - 30mA |
| NET WEIGHT (KG) | 0.155 |
| FINISH | White |
| DIMENSIONS (MM) | Height - 86 Width - 86 Depth - 40.2 Projection - 15.4 Recessed Depth - 24.8 |
| MINIMUM MOUNTING BOX DEPTH | 35mm |
| CONSTRUCTION | Construction - Thermoset resin |
| IP RATING | IP20 |
| INPUT VOLTAGE | 230V 50Hz |
| EARTH TERMINAL | Yes |
| LOAD/MAX. LOAD | 13A |
| TERMINAL TYPE | Captive |
| TERMINAL CAPACITY | 2 x 2.5mm ² or 1 x 4.0mm ² |
| ADDITIONAL FEATURES | RCD trip current of 30mA. Double pole RCD contact break. Latching type RCD. Cable outlet at bottom with strain relief. |
| FUNCTION | RCD trip speed of less than 40ms |
| WARRANTY | 2year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS 1363-4, BS 7288 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270811537 |

Date Created: 27/02/2025 15:42

