Xnightsbridge

DATASHEET



BL5BK

230V IP65 5W LED CCT Adjustable Surface Mount Brick light - Black

www.mlaccessories.co.uk



D

MLA PART CODE	BL5BK
DESCRIPTION	230V IP65 5W LED CCT Adjustable Surface Mount Brick light - Black
NET WEIGHT (KG)	0.35
FINISH	Black
DIFFUSER	Opal
DIMENSIONS (MM)	Height - 100 Width - 235 Projection - 32
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
WATTAGE (W)	5
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	495/530
LUMENS LIGHT SOURCE ONLY (LM)	820
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	152.9
CIRCUIT WATTAGE (W)	5.38
CCT	3000/4000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.025
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.147
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000





Xnightsbridge

L70B50 LIFESPAN (HRS)	60,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20mm rear and side
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 5W OUTPUT VOLTAGE - 133V OUTPUT CURRENT - 38mA POWER FACTOR - >0.9 EFFICIENCY FULL LOAD - 90 AMBIENT TEMPERATURE (Ta)5 - 50°C CASE TEMPERATURE (Tc) - 65°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270824377
Data Croated: 07/00/2005 16:20	

Date Created: 27/02/2025 16:38





