Xnightsbridge


DATASHEET



EL6060EM

230V IP20 595x595 23W/33W CCT Adjustable Troffer Panel ST Emergency

www.mlaccessories.co.uk



MLA PART CODE	EL6060EM
DESCRIPTION	230V IP20 595x595 23W/33W CCT Adjustable Troffer Panel ST Emergency
NET WEIGHT (KG)	3.3
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 595 Width - 595 Depth - 70
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	23/33
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	2895/3300/3130,4135/4500/4480
LUMENS LIGHT SOURCE ONLY (LM)	5470
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	165
LUMENS EMERGENCY MODE (LM)	280
CIRCUIT WATTAGE (W)	32.7
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.15
DISPLACEMENT FACTOR	>0.9
SVM	0.6
PST-LM	0.03
BEAM ANGLE (DEGREES)	110
L70B50 LIFESPAN (HRS)	60000





Xnightsbridge

DIMMADI E	NI .
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Voltage MAX. OUTPUT - 39W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 630/900mA EFFICIENCY FULL LOAD - 90 AMBIENT TEMPERATURE (Ta)20~+50°C CASE TEMPERATURE (Tc) - 75°C
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270865851
Data Organia de 07/00/0005 40:44	

Date Created: 27/02/2025 19:44





