Xnightsbridge

DATASHEET



SFR9940PCW

13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Polished Chrome with White Insert

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.285 FINISH Polished Chrome White Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2 MINIMUM MOUNTING BOX DEPTH CLASS I P RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY NO. OF USB PORTS NO. OF TYPE-A PORTS NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Polished Chrome With White Insert White Insert White Insert White Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) Construction - 201 Stainless steel Construction - 201 Stainless steel 25-35mm (dependent on wiring conditions) Construction - 201 Stainless steel 25-35mm (dependent on wiring conditions) 1 P20 Single Pole 230V 50Hz Single Pole 24 2.5.mm² or 1 x 4.0mm² 13A 15TERMINAL CAPACITY 15 2 x 2.5mm² or 1 x 4.0mm² 16 1	MLA PART CODE	SFR9940PCW
FINISH NSERT COLOUR White Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP PARTING IP 20 NPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 USB CHARGING WARRANTY 2 year(s) ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Yes DIMENSIONS White Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2 Width - 147.5 Depth - 34.5 Projection - 19.3 Editor - 14.5 Width - 147.5 Depth - 147.5 Depth - 34.5 Width - 147.5 Depth - 34.5 Depth - 34.5 Width - 147.5 Depth - 34.5 Dept	DESCRIPTION	13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Polished Chrome with White Insert
Misert Colour White Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP20 NPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING WARRANTY 2 year(s) ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NET WEIGHT (KG)	0.285
Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2	FINISH	Polished Chrome
DIMENSIONS (MM) Dimensions (MM) Dipth - 147.5 Depth - 24.5 Projection - 9.3 Recessed Depth - 25.2 MINIMUM MOUNTING BOX DEPTH Depth - 24.2 Construction - 201 Stainless steel Construction - 201 Stainless steel Depth - 25.2 MINIMUM MOUNTING BOX DEPTH Depth - 24.2 Secretary Indicates and I	INSERT COLOUR	White
CONSTRUCTION Construction - 201 Stainless steel CLASS I IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DIMENSIONS (MM)	Width - 147.5 Depth - 34.5 Projection - 9.3
I	MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
PRATING	CONSTRUCTION	Construction - 201 Stainless steel
SWITCH TYPE	CLASS	I
SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	IP RATING	IP20
EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY NO. OF USB PORTS NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Yes 13A 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 1 the second of the	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² 2 NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 SV DC 4.0A (shared) WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 13A 2 x 2.5mm² or 1 x 4.0mm² 2 the conformity (HELD ON FILE) 1 SV DC 4.0A (shared) 2 year(s) China	SWITCH TYPE	Single Pole
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	EARTH TERMINAL	Yes
NO. OF USB PORTS NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 2 1 2 1 2 1 2 1 2 1 2 1 2 2	LOAD/MAX. LOAD	13A
NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 1 5V DC 4.0A (shared) 2year(s) China Yes	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
NO. OF TYPE-C PORTS USB CHARGING WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 1 5V DC 4.0A (shared) 2year(s) China Yes	NO. OF USB PORTS	2
USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NO. OF TYPE-A PORTS	1
WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NO. OF TYPE-C PORTS	1
ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	USB CHARGING	5V DC 4.0A (shared)
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	2year(s)
	ORIGIN OF MANUFACTURE	China
EAN 5056270885897	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
	EAN	5056270885897

Date Created: 27/02/2025 20:03



