Xnightsbridge

DATASHEET



PM9RCD

13A 2G DP RCD Switched Socket with Outboard Rockers (Type-A) [Part M compliant]

www.mlaccessories.co.uk

MLA PART CODE	PM9RCD
DESCRIPTION	13A 2G DP RCD Switched Socket with Outboard Rockers (Type-A) [Part M compliant]
NET WEIGHT (KG)	0.237
FINISH	Anthracite
DIMENSIONS (MM)	Height - 86 Width - 146 Depth - 40.9 Projection - 14.1 Recessed Depth - 26.8
MINIMUM MOUNTING BOX DEPTH	35mm
CONSTRUCTION	Construction - Thermoset resin
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
FUNCTION	RCD trip current of 30mA. Latching type RCD. RCD trip speed of less than 40ms
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270887495

Date Created: 27/02/2025 18:25



