Xnightsbridge


DATASHEET



SA1525C

SARA 230V IP20 LED Recessed Tri-Wattage and CCT Scoop Downlight - 15/ 20/ 25W

www.mlaccessories.co.uk



MLA PART CODE	SA1525C
DESCRIPTION	SARA 230V IP20 LED Recessed Tri-Wattage and CCT Scoop Downlight - 15/ 20/ 25W
NET WEIGHT (KG)	0.88
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 157 Depth - 110 Projection - 110 Recessed Depth - 110 Minimum Void - 160
CUT-OUT (MM)	Cut-out Diameter - 140
TILT (DEGREES)	40
ROTATION (DEGREES)	350
CONSTRUCTION	Construction - Aluminium Construction 2 - & glass
CLASS	II
IP RATING	IP20
WATTAGE (W)	15 / 20 / 25
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	1440/1565/1605, 1900/2080/2125, 2335/2580/2605
LUMENS LIGHT SOURCE ONLY (LM)	3325
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	140
CIRCUIT WATTAGE (W)	23.75
ССТ	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.106





Xnightsbridge

DISPLACEMENT FACTOR	>0.9
SVM	0.014
PST-LM	0.59
BEAM ANGLE (DEGREES)	45
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-25~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 25W OUTPUT VOLTAGE - 9-42V OUTPUT CURRENT - 600mA POWER FACTOR - 0.92 EFFICIENCY FULL LOAD - 87 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270845280
Data Crasta d. 00/00/000E 00:EE	

Date Created: 28/02/2025 00:55





