Xnightsbridge

DATASHEET



M9RCD

13A 2G DP RCD Switched Socket - 30mA (Type A)

www.mlaccessories.co.uk

NET WEIGHT (KG) O.499 Powder-coated Silver/Grey NSERT COLOUR White Height - 81 Width - 142 Depth - 56.8 Projection - 56.8 CONSTRUCTION CLASS I P RATING NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL LOAD TERMINAL TYPE TERMINAL TYPE TERMINAL CAPACITY ADDITIONAL FEATURES ROBER SWARRANTY MARNUFACTURED IN ACCORDANCE WITH P ROMER SILVER O.499 Chapter White Height - 81 Width - 142 Depth - 56.8 Projection - 56.8 Construction - Premium grade steel Co	MLA PART CODE	M9RCD
POMERSIONS (MM) Powder-coated Silver/Grey White Height - 81 Width - 142 Depth - 56.8 Projection - 56.8 CONSTRUCTION PRATING IP20 NPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL TYPE CAPTIVE CAPTIVE TERMINAL TYPE CAPTIVE TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² ADDITIONAL FEATURES RCD trip current of 30mA. Latching type RCD FUNCTION RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	DESCRIPTION	13A 2G DP RCD Switched Socket - 30mA (Type A)
NSERT COLOUR White Height - 81 Width - 142 Depth - 56.8 Projection - 56.8 Projection - 56.8 CONSTRUCTION PRATING IP20 NPUT VOLTAGE CONSTRUCTION IP20 NPUT VOLTAGE CONSTRUCTION IP20 NPUT VOLTAGE CONSTRUCTION IP20 PRATING IP20 PROJUCT TYPE DOUBLE POLE EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL TYPE CAPTIVE CAPTIVE TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² ADDITIONAL FEATURES RCD trip current of 30mA. Latching type RCD FUNCTION RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	NET WEIGHT (KG)	0.499
Height - 81 Width - 142 Depth - 56.8 Projection - 56.8 CONSTRUCTION Construction - Premium grade steel Construction 2 - & thermoset resin CLASS I P RATING NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD TERMINAL TYPE Captive TERMINAL TYPE Captive TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² ADDITIONAL FEATURES RCD trip current of 30mA. Latching type RCD FUNCTION RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	FINISH	Powder-coated Silver/Grey
DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) DIPUT 1- 56.8 CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION PRATING IP20 NPUT VOLTAGE DOUBLE POLE EARTH TERMINAL Yes LOAD/MAX. LOAD 13A FERMINAL TYPE Captive FERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² ADDITIONAL FEATURES RCD trip current of 30mA. Latching type RCD FUNCTION RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	INSERT COLOUR	White
CONSTRUCTION CLASS I P RATING IP20 NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL OAD/MAX. LOAD TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION RCD trip current of 30mA. Latching type RCD FUNCTION RCD trip speed of 30ms WARRANTY VMANUFACTURED IN ACCORDANCE WITH Construction 2 - & thermoset resin I I Construction 2 - & thermoset resin I I Construction 2 - & thermoset resin I I I Construction 2 - & thermoset resin I I I I I I I I I I I I I I I I I I I	DIMENSIONS (MM)	Width - 142 Depth - 56.8
PRATING NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION RCD trip speed of 30ms WARRANTY AND TERMINAL CAPACITY BS 1363-2, BS 7288	CONSTRUCTION	Construction - Premium grade steel Construction 2 - & thermoset resin
NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION WARRANTY MANUFACTURED IN ACCORDANCE WITH Double Pole Yes Captive 3 x 2.5mm² or 2 x 4.0mm² RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms 2year(s) BS 1363-2, BS 7288	CLASS	I
EARTH TERMINAL COAD/MAX. LOAD TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION WARRANTY MANUFACTURED IN ACCORDANCE WITH TERMINAL Yes Captive 3 x 2.5mm² or 2 x 4.0mm² RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms 2year(s) BS 1363-2, BS 7288	IP RATING	IP20
TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION RCD trip speed of 30ms WARRANTY WANUFACTURED IN ACCORDANCE WITH Yes Captive 3 x 2.5mm² or 2 x 4.0mm² RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms 2 year(s) BS 1363-2, BS 7288	INPUT VOLTAGE	230V 50Hz
TERMINAL TYPE Captive TERMINAL CAPACITY ADDITIONAL FEATURES FUNCTION WARRANTY MANUFACTURED IN ACCORDANCE WITH 13A Captive 3 x 2.5mm² or 2 x 4.0mm² RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms 2year(s) BS 1363-2, BS 7288	SWITCH TYPE	Double Pole
TERMINAL TYPE Captive 3 x 2.5mm² or 2 x 4.0mm² ADDITIONAL FEATURES RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH Captive 3 x 2.5mm² or 2 x 4.0mm² RCD trip speed of 30ms EXAMPLE OF THE O	EARTH TERMINAL	Yes
TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	LOAD/MAX. LOAD	13A
RCD trip current of 30mA. Latching type RCD RCD trip speed of 30ms RCD trip speed of 30ms VARRANTY 2year(s) WANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	TERMINAL TYPE	Captive
FUNCTION RCD trip speed of 30ms 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	ADDITIONAL FEATURES	RCD trip current of 30mA. Latching type RCD
MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS 7288	FUNCTION	RCD trip speed of 30ms
<u> </u>	WARRANTY	2year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS 7288
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270811520	EAN	5056270811520

Date Created: 27/02/2025 15:41



