


DATASHEET



BLP10CCT

230V IP65 IK10 10W LED Polycarbonate Moulded Bollard - CCT Adjustable

www.mlaccessories.co.uk



MLA PART CODE	BLP10CCT
DESCRIPTION	230V IP65 IK10 10W LED Polycarbonate Moulded Bollard - CCT Adjustable
NET WEIGHT (KG)	2.25
FINISH	Black
DIFFUSER	Opal
DIMENSIONS (MM)	Height - 782 Width - 174 Depth - 174
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK10
WATTAGE (W)	10
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	655/750/700
LUMENS LIGHT SOURCE ONLY (LM)	1260/1415/1350
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	130/153/141
CIRCUIT WATTAGE (W)	9.3
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
RUNNING CURRENT (A)	0.045
DISPLACEMENT FACTOR	>0.9
SVM	0.000
PST-LM	0.03
BEAM ANGLE (DEGREES)	360
LIFE SPAN (HRS)	30,000

L70B50 LIFESPAN (HRS)	72000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20 ~ 50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 9.2W OUTPUT VOLTAGE - 108V OUTPUT CURRENT - 85mA POWER FACTOR - >0.9 AMBIENT TEMPERATURE (Ta) - 10-50°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270888225

Date Created: 27/02/2025 19:39

