Xnightsbridge


DATASHEET



BATS6UHLEM

230V 6ft 100W LED Ultra High Lumen Batten with Emergency - 4000K

www.mlaccessories.co.uk



| MLA PART CODE | BATS6UHLEM |
|-------------------------------|--|
| DESCRIPTION | 230V 6ft 100W LED Ultra High Lumen Batten with Emergency - 4000K |
| NET WEIGHT (KG) | 2.26 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1790 Width - 61 Projection - 71 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 100 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 13500 |
| LUMENS LIGHT SOURCE ONLY (LM) | 16120 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 162.05 |
| LUMENS EMERGENCY MODE (LM) | 250 |
| CIRCUIT WATTAGE (W) | 99.54 |
| ССТ | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.454 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.684 |
| PST-LM | 0.033 |
| BEAM ANGLE (DEGREES) | 120 |





Xnightsbridge

| LIFE SPAN (HRS) | 30,000 |
|--|---|
| L70B50 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | No |
| EMERGENCY | Maintained / Non-maintained / Switched |
| SELF-TEST | No |
| OPERATING TEMPERATURE | -5~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 50W OUTPUT VOLTAGE - 29-43V OUTPUT CURRENT - 1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.64 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C |
| BATTERY TYPE | LiFePO4 |
| BATTERY INCLUDED | Yes |
| WARRANTY | 5year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270821321 |
| Data Created: 07/00/000E 10:0E | |

Date Created: 27/02/2025 16:25





